



ANUCRYL C-507

TECHNICAL DATA SHEET

INTRODUCTION	ANUCRYL C – 507 is an Acrylic additive having excellent wetting and dispersing properties. It stabilizes the Emulsion paints without viscosity build up on prolonged storage.
AREAS OF APPLICATION	ANUCRYL C – 507 is a Superior Wetting and Dispersing Agent.
TYPICAL PROPERTIES	Appearance : Clear, Colourless to pale yellow liquid % Solid Content : 30 ± 1 [@ 140°C for two Hours] pH (As is) : 6.5 – 8.5 Brookfield Viscosity : 50 – 350 Cps Spindle No.2 /RPM 60@ 23°C
SAFETY DATA	Health Hazard: ANUCRYL C- 507 is a neutral nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc. while handling. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician. Fire Hazard:ANUCRYL C-507 is water based and non-flammable.
STORAGE	Store products in tightly closed original containers at temperatures recommended on the product label.
PACKAGING	240 Kg HDPE Drums/Tanker.

**HANDLING
PRECAUTION**

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,
Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in

