

## **ANUCRYL C-574**

## **TECHNICAL DATA SHEET**

INTRODUCTION

ANUCRYL C 574 is sodium salt of polycarboxylate. It has efficient wetting and dispersing property at minimal dosages. It requires less grinding time and gives higher reducing strength.

**APPLICATION** 

ANUCRYL C 574 is a High Performance Wetting and Dispersing Agent for Tinting Bases of Interior and Exterior Emulsion Paints.

TYPICAL PROPERTIES

Appearance : Yellow clear liquid

% Solid Content

@150°c for ½ hr : 36 + 1 pH as is : 8.0 - 10.0

B.F. Viscosity @30°C

Spindle No. 2/ RPM 60 : 50 - 250 Cps

**SAFETY DATA** 

Health Hazard: ANUCRYL C-574 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician. Fire Hazard: ANUCRYL C-574 is water-based and non-flammable.

**STORAGE** 

Store products in tightly closed original containers at temperatures recommended on the product label.

**PACKAGING** 

240 Kg HDPE Drums/Tanker.

## HANDLING PRECAUTION

Before using this product, consult the Material Safety Data Sheet (MSDS) for details onproduct hazards, recommended handling precautions and product storage.

## **DISCLAIMER**

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.