

ANUCRYL C-700

TECHNICAL DATA SHEET

INTRODUCTION	ANUCRYL C-700 is a styrene/ acrylic emulsion. It is highly viscous emulsion with water and alkali resistance. It has excellent adhesion to concrete and previously painted surfaces and also improves paint coverage.
APPLICATION	ANUCRYL C-700 is used for Decorative Textured Paints.
TYPICAL PROPERTIES	Appearance:Milky White liquid% Solid Content: 50 ± 1 pH (as is): $8-10$ Brook Field viscosity: $6000-10000$ CpsSpindle no. 5/ RPM 60 @ 30°cGlass Transition Temperature.17Theoretical Tg [°C]:17Flexibility:Excellent
SAFETY DATA	Health Hazard: ANUCRYL C-700 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician. Fire Hazard: ANUCRYL C-700 is water-based and non-flammable.
STORAGE	Store products in tightly closed original containers at temperatures recommended on the product label.
PACKAGING	240 Kg HDPE Drums/Tanker.

HANDLING PRECAUTION	Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.
DISCLAIMER	This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises, Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606, Maharashtra, India. Tel.: +91-22-25855379 / 25855714 Website www.anuvi.in

