### ANUCRYL

# ANUCRYL C-700 A TECHNICAL DATA SHEET

INTRODUCTION

ANUCRYL C-700 is a styrene/ acrylic emulsion. It is highly viscous emulsion with water and alkali resistance. It has excellent adhesion to concrete and previously painted surfaces and also improves paint coverage.

**APPLICATION** 

ANUCRYL C-700 is used for Decorative Textured Paints.

Appearance : Milky White liquid

% Solid Content :  $50 \pm 1$  pH (as is) : 8-10

TYPICAL Brook Field viscosity
Spindle no. 5/ RPM 60 @ 30°c

Glass Transition Temperature

Theoretical Tg [°C] : 17

Flexibility : Excellent

**SAFETY DATA** 

**PROPERTIES** 

Health Hazard: ANUCRYL C-700 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water and

6000-10000 Cps

consult a physician.

Fire Hazard: ANUCRYL C-700 is water-based and non-flammable.

STORAGE Store products in tightly closed original containers at temperatures

recommended on the product label.

PACKAGING 240 Kg HDPE Drums/Tanker.

## HANDLING PRECAUTION

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

### **DISCLAIMER**

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

#### **ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)**

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises, Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,

Maharashtra, India.

**Tel.**: +91-22-25855379 / 25855714 **Website** <u>www.anuvi.in</u>

