

ANUCRYL D-250

TECHNICAL DATA SHEET

INTRODUCTION	ANUCRYL D - 250 is new class of hydrophobic copolymer dispersant having compatibility with HASE chemistry i.e., hydrophobically modified alkali soluble emulsions. It is new specially designed for efficient wetting and dispersing property at minimal dosages with improving color acceptance.
APPLICATION	ANUCRYL D - 250 is a High Performance Wetting and Dispersing Agent for Tinting Bases of Interior and Exterior Emulsion Paints.
KEY FEATURES	 Excellent colour acceptance Improving gloss level of paints Excellent pigment wetting capabilities Very effective with organic and inorganic pigments 27% solids in ammonia form
TYPICAL PROPERTIES	Appearance: Light yellow clear liquid% Solid Content@150°c for ½ hr: 27 ± 1pH as is: 8.0 - 10.0Brook Field Viscosity @30°CSpindle No. 1/ RPM 60: 50 - 250 Cps
SAFETY DATA	Health Hazard: ANUCRYL D -250 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician. Fire Hazard: ANUCRYL D -250 is water-based and non- flammable.

STORAGE	Store products in tightly closed original containers at temperatures recommended on the product label.
PACKAGING	240 Kg HDPE Drums/Tanker.
HANDLING PRECAUTION	Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.
DISCLAIMER	This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises, Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606, Maharashtra, India. Tel.: +91-22-25855379 / 25855714 Website www.anuvi.in

