



ANUCRYL RM-629

TECHNICAL DATA SHEET

INTRODUCTION	<p>ANUCRYL RM-629 is High performance styrene acrylic polymer for road marking paints with specialized process techniques to give controlled molecular weight and narrow particle size distribution. It has fast curing and superior adhesion properties.</p>												
APPLICATION	<p>ANUCRYL RM-629 is used in Exterior Emulsion Paints as well as Road Marking Paints.</p>												
TYPICAL PROPERTIES	<table><tr><td>Appearance</td><td>: Milky white liquid</td></tr><tr><td>% Solid Content</td><td>: 50 ± 1</td></tr><tr><td>pH</td><td>: 8 – 10</td></tr><tr><td>Brook Field Viscosity Spindle no. 2/ RPM 60@ 30°C</td><td>: 500 Cps max</td></tr><tr><td>Glass Transition Temperature Theoretical Tg [°C]</td><td>: 8</td></tr><tr><td>Film Properties</td><td>: Clear and transparent</td></tr></table>	Appearance	: Milky white liquid	% Solid Content	: 50 ± 1	pH	: 8 – 10	Brook Field Viscosity Spindle no. 2/ RPM 60@ 30°C	: 500 Cps max	Glass Transition Temperature Theoretical Tg [°C]	: 8	Film Properties	: Clear and transparent
Appearance	: Milky white liquid												
% Solid Content	: 50 ± 1												
pH	: 8 – 10												
Brook Field Viscosity Spindle no. 2/ RPM 60@ 30°C	: 500 Cps max												
Glass Transition Temperature Theoretical Tg [°C]	: 8												
Film Properties	: Clear and transparent												
SAFETY DATA	<p>Health Hazard: ANUCRYL RM-629 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician.</p> <p>Fire Hazard: ANUCRYL RM-629 is water based and non-flammable.</p>												
STORAGE	<p>Store products in tightly closed original containers at temperatures recommended on the product label.</p>												
PACKAGING	<p>240 Kg HDPE Drums/Tanker.</p>												

**HANDLING
PRECAUTION**

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,
Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in

