



ANUCRYL OP-2017

TECHNICAL DATA SHEET



INTRODUCTION	ANUCRYL OP-2017 is opaque polymer. It improved light scattering efficiency and gives excellent hiding in interior coatings. It also improves gloss. It is cost effective compared to TiO ₂ .
---------------------	---

APPLICATION	ANUCRYL OP-2017 is an effective partial replacement of TiO ₂ in paint formulation.
--------------------	---

TYPICAL PROPERTIES	Appearance : Milky white liquid
	% Solid Content : 30 ± 1
	pH : 8.0 – 10.0
	B4 Ford cup Viscosity @ 30°C : 12-16 sec
	Film Properties : White

SAFETY DATA	Health Hazard: ANUCRYL OP-2017 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician. Fire Hazard: ANUCRYL OP-2017 is water-based and non-flammable.
--------------------	---

STORAGE	Store products in tightly closed original containers at temperatures recommended on the product label.
----------------	--

PACKAGING	240 Kg HDPE Drums/Tanker.
------------------	---------------------------

**HANDLING
PRECAUTION**

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,
Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in

