

ANUCRYL C-930/C-926A

GUIDELINE FORMULATION FOR ELASTOMERIC PAINT

| Chemicals | Raw Material | Raw Material Quantity |
|--------------------|----------------------|-----------------------|
| | DIW | 71.12 |
| Dispersing Agent | Anucryl C-574 | 2.03 |
| Neutralizer | AMP-95 | 0.45 |
| Carbitol | Carbitol | 20.32 |
| Thickening agent | Anucryl K-116 | 6.096 |
| | Surfactant | 1.016 |
| Defoamer | BYK-025 | 2.032 |
| DEG | DEG | 30.48 |
| TIO2 | TIO2 | 101.6 |
| CALCITE | CALCITE | 101.6 |
| BINDER | Anucryl C-930/C-926A | 640.11 |
| Defoamer | BYK-025 | 1.93 |
| Thickening agent | Anucryl K-116 | 15.24 |
| Incan Preservative | Troy | 0.081 |
| | AMP-95 | 0.5 |
| | Total | 1000 |

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,
Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in

