

# ECO-IMPRES 6006

## Cross-linking additive

### TECHNICAL DATA SHEET

<b>INTRODUCTION</b>	Eco-Impres 6006 is cross linking additive for aqueous printing inks and over print varnish.						
<b>AREAS OF APPLICATION</b>	<p>Aqueous Printing Inks and Overprint Varnishes -for improving heat resistance as well as certain degree of chemical resistance. Must take care about not allowing the ink/coating to dry on Anilox or Plate.</p> <p>Eco-Impres 6006 is a very effective acrylic resin and/or emulsion cross-linking additive for aqueous printing inks, overprint varnishes and inkjet printing inks. It has no negative influence on the runnability and does not cause any defects in the print image.</p>						
<b>TYPICAL PROPERTIES</b>	<table><tr><td>Appearance</td><td>: Clear colorless liquid</td></tr><tr><td>pH</td><td>: 11 to 13</td></tr><tr><td>Density</td><td>: 1</td></tr></table>	Appearance	: Clear colorless liquid	pH	: 11 to 13	Density	: 1
Appearance	: Clear colorless liquid						
pH	: 11 to 13						
Density	: 1						
<b>RECOMMENDED LEVELS</b>	0.5 to 2 %						
<b>PACKING</b>	20, 50 and 240 kg in HDPE containers						
<b>STORAGE, SHELF LIFE AND HANDLING</b>	Store in shadow with temperatures not exceeding 30 <sup>0</sup> C and not below 5 <sup>0</sup> C. If kept unopened and under recommended storage conditions then this product has a minimum shelf life of 12 months. Always shake before use. Always keep the lid tightly closed on the half-opened container. During the use do not put the coating to intense or vigorous agitation as this increases the tendency of foaming. If possible use peristaltic pump on the printing machine. The return pipe from the coating duct must always be touching the bottom of the coating vessel/container as this avoids excessive foaming. During the long print runs						

make an attempt to keep the coating container lid tightly closed. Coating, when wet could be cleaned with water (cold or warm water).

For the information on use of w/b coating additives, which help to modify the coating properties to suite the machine and print job requirement, please refer to our W/B coating additive guideline. This literature also helps in overcoming some of the frequently experienced coating related problems or headaches.

#### HEALTH & SAFETY

Formulation

: In accordance with BCF "Raw material selection"

Manufacture

: Bulk manufactured in accordance with BCF "Good manufacturing practice"

Hazardous Goods label

: Not required

Risk in usage. This coating will not pose any significant hazard provided reasonable standards of industrial practice are maintained

#### DISCLAIMER

The information contained in this product data sheet corresponds to our current knowledge and experience. The liability for the application and processing of this product lies with the buyer, who is also responsible for observing the third-party rights. Also, we reserve the right to alter any of the details presented here because of technical or manufacturing development

**ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)**

**Sales office:** 205/210/211, Narmada, Laxmi Industrial Premises,  
Pokharan Road No.1, Vartak Nagar, Thane - 400 606,  
Maharashtra. India.

**Tel.:** +91-22-25855379 / 25855714 **Website** [www.anuvi.in](http://www.anuvi.in)

