

10% Zinc Nap-All® Lube Grade

Rust inhibiting additive.

Physical Characteristics

Appearance	Viscous brown liquid
Metal content	Zn: 9.80 - 10.20 %
Non-volatile content	76.0 - 96.0 %
Viscosity	300 - 500 mPa.s @ 210 °F, SUS
Specific gravity	0.984 - 1.044 @ 25 °C
Color	<=18 Gardner GH
Weight per gallon	8.20 - 8.70 @ 25 °C
Flashpoint	>212 °F by Pensky-Martens Closed Cup

Features

- Formulated specifically for the lubricant industry
- 10% Zinc Nap-All® Lube Grade has an oil carrier rather than the conventional solvent carrier usually contained in Zinc Naphthenate solutions
- Acts to inhibit the formation of sludge and reduces wear scar in petroleum lubricants for compressors and refrigerator systems

Applications

- Lubricants
- Undercoating

Dosage

Please contact tech.service@borchers.com.

Storage

Protect from the effects of weathering and store at temperatures below 50 °C. Once opened, containers should be resealed immediately after each removal of the product.

Safety

Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. See SDS for further information.

811 Sharon Drive / Westlake, OH 44145 / Telephone: +1 800-321-9696 / 440-899-2950 / Fax: +1 440-808-7114 / Internet: www.borchers.com / E-Mail: info.us@borchers.com

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.