HYDROCARBON RESIN

GA-115B

Data Sheet

•	HYDROCARBON RESIN GA-115B is a low molecular weight, pale yellow thermoplastic
Established in 1975, Yuen	resin, produced from petroleum-derived monomers.

Liang is a manufacturer of Typical Properties

hydrocarbon resins, which are ■ Softening Point (R&B), °C 115+/-5 (ASTM E28)

used for making a variety of Color, Gardner 15max. (ASTM D1544)

products, including paints, 50% resin solid in toluene

rubber goods, adhesives and printing ink. Bromine Number, Br g/100g 25max. (ASTM D1159)

■ Acid Value, KOH mg/g 0.1max. (ASTM D664)

The focus of the corporation ■ Specific Gravity, @25 °C 1.05~1.10 (ASTM D71)

is sustainable, long-term

growth in new product Ash Content 0.05% max. (ASTM 2415)

improvement of the customer

1. Paint
service levels. In the production of Anti-corrosive coating, Alkyd Enamel and Vanish, widely used in the

2. Print ink

Newspapers (particularly color sections), Magazines, Folding Cartons (cereal boxes, for example), Metal Containers (cans)

3. Asphalt

ships, industry and furniture

Colorful asphalt and high speed road asphalt.

4. Rubber

In the production of rubber for shoe, inner tube and tire.

Outstanding Characteristics

It is soluble or dispersible in aromatic hydrocarbons, esters and chlorinated solvents. It is only partially soluble in ketone and insoluble in glycols and water.

Package and Supply

25 kg paper bag

■ 500 kg jumbo bag

Storage and Inventory Control

Company Information ■ Indoor storage is strongly recommended.

No. 922, Chung Shin Rd., ■ Storage at temperatures above 30°C should be avoided.

Yenchao, Kaohsiung, Taiwan, R.O.C. 🔳 All information showed in this data sheet is based on our careful examinations and investigations. We can

Tel: (+886) 7 6161234 not assume any responsibility in connection with the individual use of our products, nor do we warrant

against any loss or damages directly caused by the individual use of our products.

www.ylresin.com